

IN THE CLAIMS:

Please amend the claims as follows:

1. (ORIGINAL) A hammer wrench assembly comprising:

a hammer wrench having a hammer-end, a wrench-end and a central bar member
separating the hammer-end and the wrench-end; and,

a rotatable handle pivotally coupled to the hammer wrench between the hammer-end and
the wrench-end for holding the hammer wrench about a nut as the hammer-end is impacted with
a hammer.

2. (ORIGINAL) The assembly of CLAIM 1, wherein:

the hammer wrench further comprises a female fitting;
and,

the rotatable handle comprises a pivotal male fitting removably coupleable to the female
fitting.

3. (CURRENTLY AMENDED) The assembly of CLAIM 2, wherein the female
fitting has a first bore hole having a center axis that is aligned with a center axis of the wrench-
end; ~~and,~~

4. (ORIGINAL) The assembly of CLAIM 3, wherein said first bore hole is
perpendicular to a longitudinal center axis of the central bar member.

5. (ORIGINAL) The assembly of CLAIM 3, wherein the female fitting has a second bore hole penetrating to said first bore hole.

6. (ORIGINAL) The assembly of CLAIM 5, wherein the female fitting has a third bore hole penetrating to said first bore hole and having a same axis with, and being opposite to, said second bore hole.

7. (CANCELLED)

8. (CANCELLED)

9. (CANCELLED)

10. (CANCELLED)

11. (ORIGINAL) The assembly of CLAIM 5, wherein the male fitting comprises:
a prong adapted to mate with the first bore hole; and,
a spring-biased ball coupled to the prong for securing the prong in the first bore hole, the spring-biased ball removably coupleable to the second bore hole.

12. (ORIGINAL) The assembly of CLAIM 3, wherein the rotatable handle comprises:
an elongated central bar member;
a handle section integrally coupled to one end of the elongated central bar member; and,

a forked-end having two parallel plates for pivotally coupling therebetween the male fitting.

13. (ORIGINAL) The assembly of CLAIM 12, wherein:
the handle section comprises a slip-resistant surface; and,
the hammer-end comprises a plurality of impact surfaces.

14. (CANCELLED)

15. (CANCELLED)

16. (CANCELLED)

17. (CANCELLED)

18. (CANCELLED)

19. (CANCELLED)

20. (ORIGINAL) A hammer wrench assembly for fastening or unfastening a nut comprising:

a hammer wrench having a hammer-end, a wrench-end and a central bar member separating the hammer-end and the wrench-end;

a female fitting formed in the central bar member in close proximity to the wrench-end;
and,

a safety handle pivotally coupled to the female fitting via a male fitting, wherein pivoting the handle moves a user's hand from the proximity of the hammer end.

21. (CURRENTLY AMENDED) The assembly of CLAIM 20, wherein the female fitting has a first bore hole having a center axis that is aligned with a center axis of the wrench-end; and,

22. (CANCELLED)

23. (CANCELLED)

24. (CANCELLED)

25. (CANCELLED)

26. (CANCELLED)

27. (CANCELLED)

28. (CANCELLED)

29. (CANCELLED)

30. (ORIGINAL) The assembly of CLAIM 21, wherein the rotatable handle comprises:

an elongated central bar member;

a handle section integrally coupled to one end of the elongated central bar member; and,

a forked-end having two parallel plates for pivotally coupling therebetween the male fitting.

31. (ORIGINAL) The assembly of CLAIM 30, wherein:
the handle section comprises a slip-resistant surface; and,
the hammer-end comprises a plurality of impact surfaces.

32. (CANCELLED)

33. (CANCELLED)

34. (CANCELLED).

35. (CANCELLED).

36. (CANCELLED)

37. (CANCELLED)

38. (ORIGINAL) A method for fastening or unfastening a nut, using a hammer wrench assembly having a hammer wrench with a hammer-end and a wrench end and a pivotal safety handle pivotally coupleable to the hammer wrench in close proximity to the wrench-end, comprising the steps of:

coupling a wrench-end of the hammer wrench about the nut;

pivoting the safety handle to a location displaced away from the hammer-end;

holding the wrench-end about the nut via the safety handle;
simultaneously with the holding step, swinging a hammer to impact the hammer-end;
and,
rotating the nut with the wrench-end in a direction to fasten or unfasten the nut, in
response to the impact to the hammer-end.

39. (ORIGINAL) The method of CLAIM 38, wherein the pivoting step includes the
step of:

pivoting the safety handle to a location within approximately a 180° range.

40. (ORIGINAL) The method of CLAIM 38, wherein:
the pivoting and holding steps are performed by a first user; and,
the swinging step is performed by a second user.

41. (ORIGINAL) The method of CLAIM 38, wherein:
the pivoting, holding and swinging steps are performed by a single user.

42. (ORIGINAL) An improved hammer wrench comprising:
a hammer-end having a plurality of impact surfaces;
a wrench-end adapted to attach to a bolt head or nut; and,

a central bar member with one end integrally formed with the hammer-end, with another end attached to the wrench-end and with a female coupler between the wrench-end and the hammer-end wherein the female coupler is in close proximity to the wrench-end.

43. (CANCELLED)

44. (CANCELLED)

45. (CANCELLED)

46. (CANCELLED)

47. (CANCELLED)

48. (CANCELLED)

49. (CANCELLED)

50. (CANCELLED)

51. (CANCELLED)

52. (ORIGINAL) The improved hammer wrench of CLAIM 42, wherein said female coupler is just below said wrench-end.

53. (CANCELLED)

54. (CANCELLED)

55. (CANCELLED)

56. (CURRENTLY AMENDED) An improved hammer wrench comprising:
a hammer wrench with a hammer-end and a wrench-end; and,
a coupling means for removably coupling a handle to said hammer wrench in close
proximity to said wrench-end.

57. (CURRENTLY AMENDED) The improved hammer wrench of CLAIM 56,
wherein said coupling means comprises a female fitting for receiving a mated male fitting
attached to said handle.

58. (CANCELLED)

59. (CANCELLED)

60. (CANCELLED)

61. (CANCELLED)

62. (CANCELLED).

63. (CANCELLED)

64. (CANCELLED)

65. (CANCELLED)

66. (CANCELLED)

67. (ORIGINAL) The improved hammer wrench of CLAIM 56, wherein the wrench-

end comprises a multi-sided bore hole.

68. (CANCELLED)

69. (CANCELLED)

70. (ORIGINAL) A hammer wrench assembly comprising:
a hammer wrench with a hammer-end and a wrench-end;
a safety holding means for holding said hammer wrench at a safe distance; and,
coupling means for removably coupling said safety holding means to said hammer
wrench in close proximity to said wrench-end.

71. (ORIGINAL) The assembly of CLAIM 70, wherein said coupling means
comprises a receiving means for receiving a mated fitting means attached to said safety holding
means.

72. (ORIGINAL) The assembly of CLAIM 71, wherein said receiving means has a
mounting face which faces in a same direction as a wrench-end face of the wrench-end.

73. (CANCELLED)

74. (CANCELLED)

75. (ORIGINAL) The assembly of CLAIM 72, wherein said receiving means comprises means for attaching handles for use with socket sets to items in socket sets.

76. (CANCELLED)

77. (CANCELLED)

78. (CANCELLED)

79. (CANCELLED)

80. (ORIGINAL) An improved hammer wrench comprising:
an anvil;
a nut socket; and,
a central bar member with said anvil on one end, with said nut socket on another and opposite end and with a fitting for a safety handle between said anvil and said nut socket.

81. (ORIGINAL) The improved hammer wrench of CLAIM 80, wherein the fitting has a first bore hole having a center axis that is aligned with a center axis of the nut socket.

82. (CANCELLED)

83. (CANCELLED)

84. (CANCELLED)

85. (CANCELLED)

86. (CANCELLED)

87. (ORIGINAL) The improved hammer wrench of CLAIM 80, wherein said fitting is closer to said nut socket than to said anvil.

88. (CANCELLED)

89. (ORIGINAL) An improved hammer wrench comprising:
a hammer wrench with a hammer-end and a wrench-end; and,
a female fitting disposed in said hammer wrench between said hammer-end and said wrench-end.

90. (ORIGINAL) The improved hammer wrench of CLAIM 89, wherein the female fitting has a first bore hole having a center axis that is aligned with a center axis of the wrench-end.

91. (ORIGINAL) The improved hammer wrench of CLAIM 90, wherein said first bore hole is perpendicular to a longitudinal center axis of the hammer wrench.

92. (CANCELLED)

93. (CANCELLED)

94. (CANCELLED)

95. (CANCELLED)

96. (CANCELLED)

97. (CANCELLED)

98. (ORIGINAL) An improved hammer wrench comprising:

a hammer wrench with a hammer-end and a wrench-end; and,

a fitting for a safety handle disposed in said hammer wrench between said hammer-end and said wrench-end.

99. (ORIGINAL) The improved hammer wrench of CLAIM 98, wherein the fitting has a first bore hole having a center axis that is aligned with a center axis of the wrench-end.

100. (CANCELLED)

101. (ORIGINAL) The improved hammer wrench of CLAIM 99, wherein the fitting has a second bore hole penetrating to said first bore hole.

102. (CANCELLED)

103. (CANCELLED)

104. (CANCELLED)

105. (CANCELLED)

106. (CANCELLED)

107. (ORIGINAL) An improved hammer wrench comprising:

an anvil;

a nut socket; and,

a central bar member with said anvil on one end, with said nut socket on another and opposite end and with a female fitting between said anvil and said nut socket.

108. (ORIGINAL) The improved hammer wrench of CLAIM 107, wherein the female fitting has a first bore hole having a center axis that is aligned with a center axis of the nut socket.

109. (ORIGINAL) The improved hammer wrench of CLAIM 108, wherein said first bore hole is perpendicular to a longitudinal center axis of the central bar member.

110. (ORIGINAL) The improved hammer wrench of CLAIM 108, wherein the female fitting has a second bore hole penetrating to said first bore hole.

111. (ORIGINAL) The improved hammer wrench of CLAIM 110, wherein the female fitting has a third bore hole penetrating to said first bore hole and having a same axis with, and being opposite to, said second bore hole.

112. (CANCELLED).

113. (CANCELLED)

114. (CANCELLED)

115. (CANCELLED)